

007.144.0364

- 1 1) A method of filtering data prior to reading a digital watermark that was inserted  
2 using a scale to black technique, said method comprising the steps of first  
3 projecting the color values of each pixel onto a preferred projection axis that is  
4 determined by examining the color of the surrounding pixels, and by reading the  
5 watermark from the resulting data.  
6
- 7 2) A system for reading a digital watermark from a digital image which consists of a  
8 number of pixels, each pixel being defined by a set of numbers representing the  
9 color components of the particular pixel, a filter for calculating the value of each  
10 pixel along a preferred projection axis, and a watermark reader which operates  
11 on the values calculated by the filter.  
12
- 13 3) A method of calculating values that will be used to read a watermark from a  
14 digital image comprising the steps of: projecting the color values of each  
15 particular pixel to a preferred projection axis, said preferred projection axis being  
16 determined by averaging the colors of the pixels in an area surrounding said  
17 particular pixel.  
18
- 19 4) The method recited in claim 1 wherein the pixels in an area of three by three  
20 pixels is examined to determine the preferred projection axis.  
21
- 22 5) The method recited in claim 1 wherein said watermark has a particular tile size  
23 and wherein said the pixels in an area the size of said tile are examined to  
24 determine the preferred projection axis.  
25
- 26 6) The system recited in claim 2 wherein said filter examines the pixels in an area  
27 of three by three pixels to determine the preferred projection axis.  
28



1 13) A method of reading a digital watermark from a colored image that consists of  
 2 a plurality of pixels and which was watermarked using a scale to black  
 3 watermarking technique, said method comprising the steps of  
 4 first filtering said colored image to generate filtered data by projecting the color  
 5 values of each pixel onto a selected axis that is determined by examining the color  
 6 of the surrounding pixels, and  
 7 reading the watermark from the resulting filtered data.

8  
 9 14) A method of reading a digital watermark from a digital colored mage that  
 10 consists of a number of pixels, each pixel being defined by a set of numbers  
 11 representing the color components of the particular pixel,  
 12 filtering the value of the set of numbers that represents each pixel by projecting said  
 13 values to a selected axis, the direction of said selected axis being determined by  
 14 examining the values of the pixels in an area surrounding said pixel, and reading  
 15 said watermark from the values calculated by the filter.

16  
 17 15) The method recited in claim 14 wherein said filter determines the direction of  
 18 said selected axis for each pixel by examining the values of the pixels in a three by  
 19 three area surrounding said pixel.

20  
 21 16) A watermark reading method for reading a watermark that has been inserted  
 22 into the luminance value of the pixels of an image by projecting color changes  
 23 needed to embed said watermark onto the luminance axis of each pixel by  
 24 projecting from an axis from black to the color of the pixel, said method comprising  
 25 filtering said image prior to reading said watermark by first projecting the color  
 26 values of each pixel onto a preferred projection axis that is determined by  
 27 examining the color of the surrounding pixels, and by reading the watermark from  
 28 the resulting data.

29

- 1 17) A method of inserting first and second watermarks in an image comprising,  
2 inserting said first watermarks in said image in a first color direction and inserting  
3 said second watermark in a color direction orthogonal to the color direction of said  
4 first watermark.  
5
- 6 18) A method of reading two orthogonally inserted watermarks from an image by  
7 first filtering said image to project each pixel onto a preferred projection axis  
8 determined by the average color of the surrounding pixels and reading said first  
9 watermark from the resulting data, and then projecting each pixel onto an axis  
10 orthogonal to said preferred projection axis and reading the second watermark from  
11 the resulting data.  
12
- 13 19) The method recited in claim 17 wherein the intensity of said second watermark  
14 is lower than the intensity of said first watermark.  
15
- 16 20) A method of filtering an image containing a digital watermark to generate a set  
17 of values from which said digital watermark can be read, said digital watermark  
18 having been inserted along a particular color axis, said method comprising  
19 projecting the color values of each pixel onto a color axis which approximates the  
20 color axis used to embed said watermark in said pixel.  
21